



Requirements - Print Ready Artwork

- ▼ **The following should be observed when sending Pictographix electronic artwork:**
 - If sending raster artwork (pixel image): files must be high-resolution images (300 dpi or higher).
 - The following file formats are requested: .jpeg .png .tiff .pdf (raster)
 - If sending vector artwork: all text must be converted to outline mode (vectors) in one of the following file formats: .ai .eps .pdf (vector) .
 - Artwork must be the exact print size and orientation must match.
 - We do not print/convert .dwg Autocad files.

- ▼ Leave at least a 1/4" margin around all edges of the artwork.
Using a fill color that bleeds right to the edge of art board is acceptable (see green header below).
- ▼ When ordering AGE 3/8" acyclic stand-off plaques, an additional setup fee is applied for screw hole positioning.
All AGE artwork must be clear of artwork on all sides by 1" to accommodate flame treatment of the sign edge.
- ▼ Upload files to our server with your contact info if total file size is larger than 6MB (.ZIP / .RAR).
Send by e-mail to info@evacmap.com if less than 6MB.
- ▼ Additional setup fee is applied if screw mounting holes are required and not labeled on artwork.
- ▼ If in doubt, send us an sample of your artwork to verify that it is print-ready and meets all the requirements.

Note: Building evacuation diagrams must meet local fire and building code requirements. Contact your local fire marshal/inspector for the requirements in your area.

Example of high resolution artwork (300 dpi)

Example of low resolution artwork (72 dpi)



Cut line
Outer edge of sign.

Safe zone.
Make sure all important graphics are inside this area.

Drill hole
0.25" hole for screws + caps
(Stand-off sizes vary)

Decorative caps
Make sure caps do not cover important graphics.
19/32" diameter for Screws + caps.

